

HEAVY DUTY TOOL FOR HEAVY DUTY JOBS

● HIGH SPEED OPERATION

● TOP POWER FOR HARD WOOD APPLICATIONS

DOWN-FLOW EXHAUST
and
BUILT-IN SILENCER

BODY PROTECTOR on
ENDURING FRAME

DURABLE NOSE
and
ANTI-ABRASIVE DRIVER
for Extended Tool Life

DUST COVER
Blocks Nails or Wire Chips

CUSHIONED GRIP
ERGONOMIC FRAME
Provides Comfort during
Operation

TOUGH NYLON, FAST and EASY
LOADING MAGAZINE w/ METAL
NAIL TRAY,
Most Durable in the Industry



Air Consumption- 11.3 CFM
Noise Level dBA @ 90psi-
-Sound Pressure: 109.3
-Sound Power: 112.3

FASTENER SPECIFICATION

Collation:	15° Wire Collated
Fastener Lengths:	65~100 mm (2-1/2"~4")
Shank Diameter:	2.5~3.3mm (0.099"~0.131")
Shank Type:	Smooth, Screw, Ring
Load Capacity:	200-300

TOOL SPECIFICATION

Weight:	12.1lbs. (5.5kg)
Height:	16.4" (417mm)
Width:	6.1" (156mm)
Length:	13.3" (338mm)
Operating pressure:	70 to 120 PSI (5-8 bars)
Firing mode:	Contact Fire
Applications:	Wooden Pallet/Drum/Crate Construction, Framing

