

FinishPro32

Finish nailer









Applications


Baseboards, cabinets, case goods, chair rail, crown molding, decorative trim, door & window casing, sash and millwork, book shelves and exterior and interior trim

Features & Benefits

- Magnesium mainbody-durable & ultra-light
- Thumb wheel adjustable depth-of-drive
- Z-Clear[™] latch to removes jams fast and easy
- No-Mar pad to protect work surfaces
- 360° adjustable exhaust keeps oil and dust away from the work surface
- Belt hook lets the tool go where you go
- Comfort grip for comfort and control

Technical specifications		
Dimension (LxWxH)	307x76x276 mm	
Net weight	1,9 kg	
Firing mode	Restrictive	
Air inlet	1/4" female NPT	
Operating pressure	4,8 - 8,3 bar	
Air consumption (at 60 shots per minute)	61,2 l/m	
Operating temperature range	-18 - 49 °C	
Sound pressure level (Lpa)	84 dB	
Sound power level (Lwa)	97 dB	
Shots / second	3	
Magazine capacity	110 pieces	
Gauge	16 ga.	
Collation type 1	Glue collated	
Collation angle	0 o	

Fastener specification



Description	Art. Nr.	EAN code
FinishPro32, finish nailer 1,6mm (RX)	1X2201N	0741474058851