

# SENCO®

MAKING HARD WORK  
**EASIER**

# FinishPro42XP



## Finish nailer

### Technical specifications

Dimension (LxWxH)	330x89x292 mm
Net weight	2,1 kg
Firing mode	Restrictive
Air inlet	1/4" female NPT
Operating pressure	4,8 - 8,3 bar
Air consumption (at 60 shots per minute)	133 l/m
Operating temperature range	-18 - 49 °C
Sound pressure level (Lpa)	89 dB
Sound power level (Lwa)	94 dB
Vibration level	<2,5 m/s <sup>2</sup>
Shots / second	5
Magazine capacity	104 pieces
Gauge	15 ga.
Collation type 1	Taped strip
Collation angle	34 °


### Applications

Baseboards, cabinets, case goods, caskets, chair rails, decorative trim, door & window casing, sash & millwork, exterior trim, finish applications/trim, furniture and paneling.

### Features & Benefits

- Rugged internal engine design
- NeverLube® technology – no lubrication required
- Magnesium housing - lightweight and comfortable to use all day
- Thumb wheel adjustable depth-of-drive
- Comfort grip
- EZ-Clear™ latch – to clear jams fast
- 360° adjustable exhaust
- Two No-Mar pads with onboard storage to protect work materials
- Advanced belt hook – convenient storage

### Fastener specification



### Description

FinishPro42XP, finish nailer 1,8mm (DA)

### Art. Nr.

4G2003N

### EAN code

0741474040771