

HEAVY DUTY TOOL FOR HEAVY DUTY JOBS

- HIGH SPEED OPERATION
- AVAILABLE WITH CONTACT FIRE TRIGGER
- TOP POWER FOR HARD WOOD APPLICATIONS
- SHOCK-ABSORBENT AUXILIARY SIDE HANDLE



DOWN-FLOW EXHAUST
and
BUILT-IN SILENCER

BODY PROTECTOR on
ENDURING FRAME

REMOVABLE SIDE HANDLE
For Absolute Control

DURABLE NOSE
and
ANTI-ABRASIVE DRIVER
for Extended Tool Life

CUSHIONED GRIP
ERGONOMIC FRAME
Provides Comfort during
Operation

TOUGH NYLON, FAST and EASY
LOADING MAGAZINE w/ METAL
NAIL TRAY,
Most Durable in the Industry

Air Consumption- 11.3 CFM
Noise Level dBA @ 90psi-
-Sound Pressure: 110.0
-Sound Power: 111.2

FASTENER SPECIFICATION	
Collation:	15° Wire Collated
Fastener Lengths:	90~130 mm (3-1/2"~5-1/8")
Shank Diameter:	3.3~3.8mm (0.131"~0.150")
Head Diameter:	7.5~8.6mm (0.295"~0.338")
Shank Type:	Smooth, Screw, Ring
Load Capacity:	120-225

TOOL SPECIFICATION	
Weight:	13.2lbs. (6.0kg)
Height:	18.4" (467mm)
Width:	6.1" (156mm)
Length:	13.3" (338mm)
Operating pressure:	70 to 120 PSI (5-8 bars)
Firing mode:	Contact Fire
Applications:	Wooden Pallet/Drum/Crate Construction, Framing

