

- **SM44HD**

- Automatic four-flaps-folder device
- Side drive belts (2 x 75 mm width each)
- Drive belts speed 30 m/min.
- 2 motors kW 0,18 each
- Side pressure rollers to control flaps box closing
- Pneumatic detector system boxes height
- 2 x K11R taping unit - 50 mm width
- Low/brake tape device
- Side safety protections connected to electro-pneumatic disconnection switches
- Safety protection grids
- Control panel for pneumatic adjustment
- Integrated control panel
- Air pressure regulator
- Average air pressure consumption: 180 NI/min approx.
- Production capacity up to 450 boxes/hour
- AS24HD centering unit with box holder
- Box dimensions\*
- Min. L 200 mm W 160 mm H 140 mm
- Max. L 600 mm W 500 mm H 500 mm
- *\*Other possible configurations for larger or smaller boxes*

- **SM44HS**

- Automatic four-flaps-folder device
- Side drive belts (2 x 75 mm width each)
- Drive belts speed 30 m/min.
- 2 motors kW 0,9 each
- Side pressure rollers to control flaps box closing
- Electro/pneumatic detector system boxes height
- 2 x K11R taping unit - 50 mm width
- Low/brake tape device
- Side safety protections connected to electro-pneumatic disconnection switches
- Safety protection grids
- Control panel for pneumatic adjustment
- Integrated control panel
- Average air pressure consumption: 350 NI/min approx.
- Production capacity up to 800 boxes/hour
- AS26HS indexing unit with box holding device
- Box dimensions\*
- Min. L 200 mm W 160 mm H 140 mm
- Max. L 600 mm W 500 mm H 500 mm
- *\*Other possible configurations for larger or smaller boxes*