

DS5525-18V

DuraSpin screwdriver















Applications

Drywall (to wood or steel studs), Cement board, Underlayment, Sheating to steel, Metal framing, Structural steel decking, Rigid foam insulation

Features & Benefits

- 2500 RPM high-speed motor
- 18v Li-ion technology (Includes 2 batteries)
- Patent pending corner-fit feed system
- Tool-free screw length adjustment
- Precise depth-of-drive adjustment with depth lock
- Quick slide button bit change
- Variable speed trigger with lock and reverse
- Belt hook -right or left handed adjustable

| Technical specifications | | |
|----------------------------|----------------------|--|
| Dimension (LxWxH) | 381x86x241 mm | |
| Net weight | 2,19 kg | |
| Sound pressure level (Lpa) | 76 dB | |
| Sound power level (Lwa) | 87 dB | |
| Vibration level | 0,8 m/s ² | |
| Magazine capacity | 50 pieces | |
| Battery type | Li-Ion | |
| Battery voltage | 18 V | |
| Battery ampere rating | 3 Ah | |
| Battery power | 54 W | |
| Recharge time 80% | 15 minutes | |
| Recharge time 100% | 45 minutes | |
| Shots per charge | 1400 | |
| Number of batteries in kit | 2 pieces | |
| Voltage (ac) | 230 V | |
| Frequency | 50 Hz | |
| Electrical plug type | Continental | |
| Rotations per minute (RPM) | 2500 RPM | |

Fastener specification



| Description | Art. Nr. | EAN code |
|----------------------------------|----------|---------------|
| DS5525-18V, DuraSpin Screwdriver | 7X2001N | 8718035005182 |