

MAKING HARD WORK EASIER

NS20XP



Applications

Sheathing, furniture framing, roof decking, subflooring, crate and box assembly, pallets, cedar shingles, furring, metal tie-down straps, fascia and soffits, ridge beam assembly


Features & Benefits

- 15% more powerful than all other construction staplers in its class. Well-balanced, ergonomic design for all-day use
- Rotatable belt hook
- Enhanced EZ-Clear latch allows for quick access to clear fasteners
- New drive track design eliminates movement of the staple, enhancing overall drive performance and virtually eliminating fastener jams, skipping and misfires.

Heavy wire stapler

Technical specifications		
Dimension (LxWxH)	381x89x279 mm	
Net weight	2,3 kg	
Firing mode	Dual	
Air inlet	3/8" female NPT	
Operating pressure	4,8 - 8,3 bar	
Air consumption (at 60 shots per minute)	113 l/m	
Operating temperature range	-18 - 49 ºC	
Sound pressure level (Lpa)	84 dB	
Sound power level (Lwa)	97 dB	
Vibration level	2,3 m/s ²	
Magazine capacity	160 pieces	
Gauge	16 ga.	
Collation type 1	Glue collated	
Collation angle	0 o	

Fastener specification



Description	Art. Nr.	EAN code
NS20XP, hw stapler	9X2001N	8715274237862